

SmartSource® Professional



SmartSource Professional

You have evolving demands; we have a platform to meet them. Burroughs Payment Systems, known for item processing quality and reliability for over 100 years, now provides the SmartSource Professional. Based upon a common platform, the SmartSource family of scanners is driven by the powerful Burroughs Device Suite, a web-based interface for all distributed capture devices offered by Burroughs.

The SmartSource is available in product lines:

- Value
- Professional
- Expert

A common platform standardizes the development of application software, user training, technical help desk and

supplies management – streamlining operations and improving efficiency. This common support infrastructure provides the foundation for introducing or expanding your remote deposit capture environment. Our multiple devices and variety of configurations allow you to meet your unique processing needs - creating a competitive advantage that is vital in today's business environment.

SmartSource Professional

The SmartSource Professional is a perfect fit in any PC-based environment. Its extensive set of features offers unparalleled flexibility. Choose your speed, hopper size, and endorsement along with other unique options designed to meet your processing requirements. Many features can be upgraded at your location (on-line) as your business needs expand.

SmartSource Professional Specifications

| | |
|---|---|
| Document Processing Throughput | Dimensions |
| Document throughput of 30, 55, 80 or 120 documents per minute (dpm) | Length: 10.5 in (26.7 cm) Depth: 5.99 in (16.0 cm) Height: 7.0 in (17.8 cm) |
| Power Requirements | Document Hopper |
| 100-240 VAC @ 50/60 Hz | Up to 100 item hopper capacity |
| Weight | Document Feeder |
| Installed weight: 6.5 lbs. (3.0 kg) Power supply: 0.75 lbs. (0.34 kg) | Automatic document feeder One (1), 50 or continuous document feed Double document detection |
| Certifications | Magnetic Ink Character Recognition (MICR) |
| CE, UL/TUV, CSA, RoHS, VCCI, Energy Star, FCC Class B | E13B and CMC7 read with auto-detect |
| Document Sizes | Image Capture |
| Document size - Height (min./max.): 2.50 to 4.25 inches (6.35 to 10.80 cm) - Length (min./max.): 4.50 to 9.25 inches (11.4 to 23.5 cm) Document weight - Paper weight, nominal: 20 to 24 lb - 20 lb. long grain (75 gr/m ²) - 24 lb. short or long grain (90 gr/m ²) Document Height-to-Length ratio - Minimum aspect ratio: 1.50 | Front and rear image capture at 300 dots per inch (dpi) Two (2) color images or a combination of up to three (3) bi-tonal and gray scale images Image renditions available - Bi-tonal (black/white) - Gray level (256 gray shades) - Color (24-bit, RGB) – Device Suite only Image resolutions available - 300 dpi, color only (reduced throughput) – Device Suite only - 240, 200 dpi, gray level or bi-tonal - 120, 100 dpi, gray level |
| Communication Interface | Image Compression Standards |
| USB 2.0 high-speed | CCITT Group 4 (bi-tonal images) JPEG Baseline (gray level images) Uncompressed 24-bit, RGB pixel data (color images) – Device Suite only |
| Operating Systems | Optical Character Recognition (OCR) |
| Windows XP Professional 32-bit Windows VISTA Business 32 and 64-bit Windows 7 Professional 32 and 64-bit Linux (Ubuntu 9.04, 32-bit, Ubuntu 9.10, 32-bit, Fedora 12, 32-bit) | OCR-A, OCR-B and E13B fonts supported Two (2) 0.50 inch OCR scan bands provided 96 characters per scan band MICR/OCR combine read |
| Operator Interface | Endorsement |
| Power switch Feeder start/stop button Light Emitting Diode (LED) - Three (3) LED status lights | Front Franker - Franking roller with fixed message - Franking actuation, controlled programmatically Rear Endorser - Ink jet print cartridge (600 dpi) - One (1) to four (4) line endorsement, 10 characters per inch - Two (2) vertical endorsement locations, manually selected by operator allows eight (8) single-line vertical endorsement locations - Graphics capable for logos and signatures - Three (3) levels of print quality (economy, standard, or premium) - Programmatically controllable based on MICR and/or OCR read - True type fonts |
| Application Programming Interfaces (API) | Output Pockets |
| CAPI (Common Application Programming Interface) Device Suite Professional PC version Emulation Middleware Ranger® for SmartSource Twain CAPI for Linux | Single or dual pocket configuration available 100 item pocket capacity per pocket Pocket selection based on MICR/OCR read results |

For more information about the entire line of Burroughs remote capture products, visit us at www.burroughs.com

Burroughs is a registered trademark licensed to Burroughs Payment Systems, Inc. in the United States and other countries. SmartSource is a registered trademark of Burroughs Payment Systems, Inc. Ranger is a registered trademark of Silver Bullet Technology, Inc. All other brands and products referenced in this document are acknowledged to be the trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.